

Mirka Glass Polishing Solution



Description

1 x Mirka PS1437 Electric Polisher

1 x Backing Pad for PS1437

1 x Dust suction hood for PS1437

1 x Pack of 5 Abranet® SIC NS 125mm discs P80

1 x Pack of 5 Abranet® SIC NS 125mm discs P120

1 x Pack of 5 Abranet® SIC NS 125mm discs P150

1 x Pack of 5 Abranet® SIC NS 125mm discs P180

1 x Pack of 5 Abranet® SIC NS 125mm discs P240

1 x Pack of 5 Abranet® SIC NS 125mm discs P320

1 x Pack of 5 Abranet® SIC NS 125mm discs P400

1 x Pack of 2 Abralon® 125mm discs P180

1 x Pack of 2 Abralon® 125mm discs P360

1 x Pack of 2 Abralon® 125mm discs P500

1 x Pack of 2 Abralon® 125mm discs P600

1 x Pack of 2 Abralon® 125mm discs P1000

1 x Pack of 2 white felt polishing pad

1 x Pack of 2 microfibre cleaning cloth

1 x 250ml bottle of Polarshine E3 polishing compound

£545.45 List Price

Always clean and inspect between each stage using Mirka Clay Lubricant and Microfibre Cloth.







Action: Check and clean at each grit stage to be sure previous grits scratches have been removed.

discs grits P150 or

Use: Abranet SIC NS

Action: Remove

finer through to P400. Always finish with



Action: Further reduce scracthes and repair edge. Expand the repair area with finer Abralon discs.

flat to help the edge

Action: During the Abralon stages, the machine must remain

blending process.

Use: Abralon discs P360 to P1000.



Action: Polish the repair, making around three passes with the compound. Keep to small areas at a time.

Action: Check edge definition of repair, making sure edges are

Use: E3 Glass polishing compound with Mirka felt polishing pad.

clouding.

beginning to blend.
Dampen to reduce

Use: Abralon P1000 and Mirka lubricant.



Action: Keep the felt Polishing pad clean to avoid polish build up resulting in a poor finish.



Action: Clean and inspect. Re-polish if needed for final result.
Use: Mirka lubricant and microfibre cloth.

DO NOT EXCEED SUGGESTED
TEMPERATURE.

